

Powder Products / Manufacturers		Duralloy 272 D610	Duratec 900 D2010	Duratec LX 905 D2015	Fluoroset FP 964 D3000 Fluoromax
Conditions	Coatings Grade	High Durability	Super Durable	Super Durable Enhanced	Ultra Durable
Licensed Applicator Level Required to Pretreat & Process this Powder Class		<input checked="" type="checkbox"/> AAF is Licensed to this HD Applicator Level	<input checked="" type="checkbox"/> AAF is Licensed to this SD Applicator Level	<input checked="" type="checkbox"/> AAF is Licensed to this SDE Applicator Level	<input checked="" type="checkbox"/> AAF is Licensed to this UD Applicator Level
Building & Location Warranty Pre-approval Building: No. Floors Build'g Code of Australia (BCA) Class Dist. to Saltwater Atmospheric Classifications (AS3715)		Pre-approval Req'd 1-3 Flrs. & Single Occupancy 1 or 10 > 100m Mild, Tropical Only	Pre-approval Req'd Any Number All Classes > 10m. All Classifications	Pre-approval Req'd Any Number All Classes > 10m. All Classifications	Pre-approval Req'd Any Number All Classes > 10m. All Classifications
Suitable substrates Pretreatment, Rinse & Process Control Maintenance Requirement		Aluminium Only Qualicoat Approved Refer AS3715	Aluminium Only Qualicoat Approved Refer AAMA 610	Aluminium Only Qualicoat Approved Refer AAMA 610	Aluminium Only Qualicoat Approved Refer AAMA 610
AAF Warranty Plus Offering					
Colour & Gloss Integrity		Not Offered Not Offered	10 10	10 or 15 15	20 20
Integrity for AAF EverGuard Pretreatment		Not Offered	Extra 5 Years	Extra 5 Years	Extra 5 Years
Performance Specifications					
Pigments & Binder		Organic Pigments	Ceramic Pigments	Ceramic Pigments & High Binder Ratio	Ceramic Pigments & Highest Binder Ratio
Powder Satisfies: Australian Standard & American Architectural Mfr's Assoc Std.		AS3715 AAMA2603	AS3715 AAMA2604	AS3715 AAMA2604	AS3715 AAMA2605
AAMA Test - 45° Florida Exposure		1 Year	5 Years	5 Years	10 Years
AAMA Test - Gloss Retention		N/A	Min. 30%	Min. 30%	Min. 50%
AAMA Test - Colour Retention		N/A	< 5 Delta E	< 5 Delta E	< 5 Delta E
AAMA Tests - Saltspray & Humidity		1,500 hrs	3,000 hrs	3,000 hrs	4,000 hrs